



UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/531,575	04/18/2005	Takashi Noro	123532	1882
<div>25944 7590 12/31/2007 OLIFF & BERRIDGE, PLC P.O. BOX 320850 ALEXANDRIA, VA 22320-4850</div>				
EXAMINER				
LAMB, BRENDA A				
ART UNIT		PAPER NUMBER		
1792				
MAIL DATE		DELIVERY MODE		
12/31/2007		PAPER		

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

Office Action Summary	Application No.	Applicant(s)	
	10/531,575	NORO ET AL.	
	Examiner	Art Unit	
	Brenda A. Lamb	1792	

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

Status

- 1) ☒ Responsive to communication(s) filed on 9/10/2007.
- 2a) ☐ This action is **FINAL**. 2b) ☒ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

Disposition of Claims

- 4) ☒ Claim(s) 16-30 is/are pending in the application.
- 4a) Of the above claim(s) _____ is/are withdrawn from consideration.
- 5) ☐ Claim(s) _____ is/are allowed.
- 6) ☒ Claim(s) 16-30 is/are rejected.
- 7) ☐ Claim(s) _____ is/are objected to.
- 8) ☐ Claim(s) _____ are subject to restriction and/or election requirement.

Application Papers

- 9) ☐ The specification is objected to by the Examiner.
- 10) ☐ The drawing(s) filed on _____ is/are: a) ☐ accepted or b) ☐ objected to by the Examiner.
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

Priority under 35 U.S.C. § 119

- 12) ☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
- a) ☐ All b) ☐ Some * c) ☐ None of:
1. ☐ Certified copies of the priority documents have been received.
 2. ☐ Certified copies of the priority documents have been received in Application No. _____.
 3. ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).
- * See the attached detailed Office action for a list of the certified copies not received.

Attachment(s)

- | | |
|---|---|
| 1) <input checked="" type="checkbox"/> Notice of References Cited (PTO-892) | 4) <input type="checkbox"/> Interview Summary (PTO-413)
Paper No(s)/Mail Date. _____ |
| 2) <input type="checkbox"/> Notice of Draftsperson's Patent Drawing Review (PTO-948) | 5) <input type="checkbox"/> Notice of Informal Patent Application |
| 3) <input checked="" type="checkbox"/> Information Disclosure Statement(s) (PTO/SB/08)
Paper No(s)/Mail Date <u>11/27/07</u> . | 6) <input type="checkbox"/> Other: _____ |

The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negated by the manner in which the invention was made.

This application currently names joint inventors. In considering patentability of the claims under 35 U.S.C. 103(a), the examiner presumes that the subject matter of the various claims was commonly owned at the time any inventions covered therein were made absent any evidence to the contrary. Applicant is advised of the obligation under 37 CFR 1.56 to point out the inventor and invention dates of each claim that was not commonly owned at the time a later invention was made in order for the examiner to consider the applicability of 35 U.S.C. 103(c) and potential 35 U.S.C. 102(e), (f) or (g) prior art under 35 U.S.C. 103(a).

Claims 16-30 are rejected under 35 U.S.C. 103(a) as being unpatentable over Fukuta et al.

Fukuta et al teaches a process and apparatus of a coating apparatus which is comprised of the following elements: a holding means which holds the pillar structure in nearly vertical direction and rotates together with the held pillar structure on an axis of nearly vertical direction as a common rotating axis, a supplying and coating means which is disposed at a given position with respect to the outer peripheral surface of the pillar structure and supplies a coating material to the outer peripheral surface of the

rotating pillar structure and coats the coating material on the outer peripheral surface, and a smoothing means which smoothes the coating surface of the coating material supplied to and coated on the outer peripheral surface, wherein the supplying and coating means has a nozzle having an opening in the form of a slit for supplying the coating material toward the outer peripheral surface and coating the coating material thereon and the opening of the nozzle is disposed in nearly vertical direction with the position of the upper end of the opening being nearly the same as the position of the upper end of the pillar structure and, and the smoothing means is disposed in nearly vertical direction in such a state as keeping a given distance from the outer peripheral surface or contacting with the outer peripheral surface, and wherein the coating material is supplied from the opening of the nozzle to the upper side of the outer peripheral surface of the pillar structure and coated thereon, and the coating surface of the coating material supplied and coated is smoothed between the outer peripheral surface and the longer side end portion of the smoothing means to form a uniform coating surface on the whole outer peripheral surface of the pillar structure. Fukuta et al teaches the length of the pillar structure being coated by the coating apparatus varies and teaches at least one of the upper and lower pallet is vertically movable along guide rails to obviously accommodate substrate having different length to be held there between. Fukuta et al teaches at column 4 lines 5-12 that the length of the smoothing means in the longer direction is such that it may touch the upper and lower pallet of the holding means. Fukuta et al shows in his Figures that the slot of the supplying and coating means is shorter in length relative to the smoothing means. Fukuta et al fails to teach the length

of the nozzle opening along its longitudinal axis is less than or is shorter than the length between the both ends of the pillar structure. Therefore, given the silence of Fukuta et al of changing the nozzle assembly to correspond to a different length of structure to be coated and the height adjustability of at least one the pallets along the pair of guide rails 2 which extend a length which is substantially equivalent length of the smoothness means or doctor blade, it would have been prima facie obvious that the Fukuta et al apparatus can coat a variety of heights of pillar structures including one such that its length relative to the length of the slot of the Fukuta et nozzle assembly and doctor blade of the Fukuta et al smoothing means is within the scope of the claim for the obvious reason of reason of greater control of the coating process. Fukuta et al is capable of coating a structure within the scope of claim since it teaches every claimed element of the apparatus. Thus claim 15 is obvious over Fukuta et al. With respect to claim 17, Fukuta et al apparatus is capable of holding elongate structures having a range of different lengths including one wherein the length of the nozzle relative to elongate structure is within the scope of the claim via height adjustment of the at least one of the upper and lower pallet. With respect to claim 18, Fukuta et al teaches the holding means has a pedestal which holds the pillar structure in the vertical direction placed thereon with one end thereof facing downward. With respect to claim 19, Fukuta et al teaches the holding means has a cam which presses downwardly another end of the pillar structure held on the pedestal and rotates on the axis of the nearly vertical direction as a common rotating axis. With respect to claim 20, Fukuta et al teaches the outer peripheral shape of the pedestal and that of the cam are nearly the same. With

respect to claim 21, Fukuta et al teaches the apparatus is further comprised of a centering means which holds the pillar structure and the pedestal and/or the cam in a given positional relation. With respect to claim 22, Fukuta et al teaches the apparatus is further comprised of a following means as shown in Figure 2 which drives the smoothing means following the outer periphery of the pedestal and/or the cam so that the smoothing means is disposed at a given position with respect to the outer peripheral surface of the pillar structure. With respect to claim 23, Fukuta et al teaches the following means has first and second following rollers which are disposed at a given distance from each other and move backward and forward following the outer periphery of the cam while contacting with the outer periphery of the cam together with the supplying and coating means and the smoothing means, and the first and second following rollers are disposed so that the angle formed by a line passing through the centers of the respective rollers and the smoothing means is a given angle. With respect to claim 24, Fukuta et al teaches the following means further has third and fourth following rollers which move backward and forward following the outer periphery of the pedestal while contacting with the outer periphery of the pedestal together with the supplying and coating means and the smoothing means, and the rotating axis of the third following roller and that of the first following roller are common and the rotating axis of the fourth following roller and that of the second following roller are common. With respect to claim 25, Fukuta et al teaches the outer periphery of the pedestal and/or the cam is comprised of a stainless steel or ceramics. With respect to claim 26, Fukuta et al teaches the smoothing means comprises stainless steel or wear-resistant ceramics.

With respect to claim 27, Fukuta et al teaches the shape of a section of the pillar structure cut along a plane perpendicular to the direction of the central axis of the pillar structure is circular or elliptical. With respect to claim 28, Fukuta et al is capable of coating a pillar structure which is a honeycomb structure comprising a plurality of cells which serve as flow paths for fluid since it teaches every element of the claimed apparatus. With respect to claim 29, Fukuta et al teaches the supplying and coating means and the smoothing means can rotate together along the outer periphery of the pillar structure. With respect to claim 30, Fukuta et al teaches a method for coating outer peripheral surface of a pillar structure wherein the method is comprised of the following steps of holding the pillar structure by the holding means, the supplying and coating means on the outer peripheral surface of the pillar structure and coating the coating material thereon while rotating the pillar structure and the holding means on the axis of nearly vertical direction as a common rotating axis, and smoothing the coating surface of the supplied and coated coating material between the outer peripheral surface and the longer side end portion of the smoothing means. Fukuta et al fails to teach the length of the nozzle opening along its longitudinal axis is less than or is shorter than the length between the both ends of the pillar structure. Therefore, given the silence of Fukuta et al of changing the nozzle assembly to correspond to a different length of structure to be coated and the height adjustability of at least one the pallets along the pair of guide rails 2 which extend a length which is substantially equivalent length of the smoothness means or doctor blade, it would have been prima facie obvious to provide the Fukuta et al nozzle assembly with a length that is shorter than

some of the taller length structures to be coated in order prevent coating of the support structure which includes the upper and lower pallet when supporting the shorter length structures.

The following is a quotation of the second paragraph of 35 U.S.C. 112:

The specification shall conclude with one or more claims particularly pointing out and distinctly claiming the subject matter which the applicant regards as his invention.

Claims 1-30 rejected under 35 U.S.C. 112, second paragraph, as being indefinite for failing to particularly point out and distinctly claim the subject matter which applicant regards as the invention.

Claim 1 is confusing since it unclear what the apparatus for coating the pillar structure is comprised of. It is suggested that applicant at line 2 of claim1 before "a holding means" delete "provided with" and insert -- comprised --. The term "the cam" at line 3 of claim 21 and claim 22 lacks proper antecedent basis.

Applicant's arguments with respect to claims have been considered but are moot in view of the new ground(s) of rejection.


Any inquiry concerning this communication or earlier communications from the examiner should be directed to Brenda A. Lamb whose telephone number is (571) 272-1231. The examiner can normally be reached on Monday-Tuesday and Thursday with alternate Wednesdays and Fridays off.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Nadine Norton, can be reached on (571) 272-1465. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Application/Control Number:
10/531,575
Art Unit: 1792

Page 8

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <http://pair-direct.uspto.gov>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free).

A handwritten signature in black ink, appearing to read "Brenda A Lamb", written in a cursive style.

Brenda A Lamb
Examiner
Art Unit 1734